

LOC I-PBV	APP CRS	Rwy Idg	4982
110.1	111°	TDZE	128
		Apt Elev	128

ILS or LOC RWY 11

ST GEORGE (PBV) (PAPB)


⚠

DME from SRI NDB/DME. Simultaneous reception of I-PBV and SRI DME required. Circling NA north of Rwy 11-29. ADF and DME required. Inop table does not apply to S-LOC 11 Cats A and B and S-ILS 11 all Cats.

MALSF

MISSED APPROACH: Climb to 3200 on SRI NDB/DME bearing 110° to LIJFY/SRI 7.7 DME and hold, continue climb-in-hold to 3200.

ASOS 135.45	ANCHORAGE CENTER 119.1 339.8	CTAF 122.8
----------------	---------------------------------	---------------



ELEV 128

TDZE 128

111° 5 NM from FAF

4982 X 1.50

29

REIL Rwy 29

HIRL Rwy 11-29

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

ADF and DME REQUIRED

Remain within 10 NM

APOTE SRI 6

WVOG SRI 3.3

3200 SRI 110°

LIJFY SRI 7.7

* LOC only

3000

291°

2100

111°

2100

*1060

GS 3.60° TCH 56

SRI 2.7

SRI 1

SRI NDB/DME

2.7 NM

0.6 NM

1.7 NM

CATEGORY	A	B	C	D
S-ILS 11	428-1	300 (300-1)		NA
S-LOC 11	840-1	712 (800-1)	840-1¾ 712 (800-1¾)	NA
CIRCLING	840-1 712 (800-1)	980-1¼ 852 (900-1¼)	980-2½ 852 (900-2½)	NA

AK, 17 APR 2025 to 12 JUN 2025

AK, 17 APR 2025 to 12 JUN 2025